




12W FRD LED DOWNLIGHT
Front CCT Switchable Fire-Rated Downlight




12W
1000lm




Dimmable




Fire rated
AS1530 part 4



Beam angle
90°



cutout
90mm



IC
rated



Acoustic
rated

- Front CCT switchable option, 3000K & 4000K & 6000K
- IC-F Insulation coverable
- TRIAC Dimming match with HPM ,Legrand, Clipsal... Dimmer
- Twist and Lock facial change to White/Chrome/Brushed
- Fire Rated standard in accordance with AS1530.4/BS476-21
- SAA & C-tick approved from JAS-ANZ accredited lab house



Tri-color Temp



• 3000K Warm white



• 4000K Cool white



• 6000K Day light



Item	Fire Rated Downlight	Cut Out	Φ90 mm
Part No.	5RS086	Driver	Isolated Constant Current
Power	12W	Dimmable	Trailing Edge
Output	920LM	Energy Class	A+ 12kWh/1000hr
Input	AC 220-240V~50Hz	Size	Drawing Supplied
CRI	80	Warranty	5 Years
Beam Angle	90°	LED	SMD
Lifespan	50,000hrs	Switch Cycles	100,000
House Material	Aluminium	Insulation Coverable	YES
PF	0.9	Operating Temp.	-30°C~45°C
Fire-rated	AS1530.4 & BS476-21	Certification	SAA, C-tick ,CE ROHS

