



PRODUCT CATALOG

DOWNLIGHT COLLECTION 2018





WELCOME

About US

SPECIALIST ODM SUPPLIER OF LED DOWNLIGHT PRODUCTS

Radiant Lighting has its factory located in Suzhou city which is about 2hrs driving time to Shanghai. Established in 2005, Radiant is a group of high-tech enterprises that specialize in the research and development, production, sales and service of professional led downlight products.

With 30 R&D staff members, Radiant customizes for your market. All product sold by Radiant is tool opened product and has its own innovation added to the value. Radiant can offer one stop service from product design, tooling, package design and video creation.

Factory covers an area of 9000 square meters and has more than 180 staffs. We can deliver bulk order in 20 days and are flexible for small orders and urgent delivery.

Radiant takes responsibility and do the best to comply to it. Factory operation fully follows the standards of ISO9001, ISO4001 and BSCI. And 6S administration is very well performed in the factory. Clear, tidy and in order impression is what we can always deliver to those who has visited us.

We believe that our people are the heart of Radiant Lighting and that we have talent, infrastructure and the commitment to serve our customers to the highest standards. We respect copy rights, innovation and creation.

Welcome to inquiry and visit Radiant Lighting.



TRANO
entst

RADIANNA
Lighting

A close-up, black and white photograph of a textured surface, possibly a piece of fabric or a material used in manufacturing. The texture is fine and granular. In the upper left quadrant, there is a faint, embossed logo consisting of a stylized 'M' shape with a horizontal line extending to the right, resembling a modern architectural or industrial symbol.

WHY CHOOSE US?

Product Quality

All of our LED downlight products are manufactured in specialised custom-built facilities to ISO 9001 quality standards and use only high quality components in their construction.

Custom Design

Our professional design and engineering teams can create customised products that enable customers to differentiate from competitors and achieve maximum value in their local markets.

Project Management

We assign dedicated project managers to ensure that every aspect of manufacturing, assembly and quality control is progressed to meet individual customer specifications.

Customer Service

Our multi-lingual customer service managers work to accurately understand the requirements of all customers and provide industry leading service standards before, during and after contracts complete.

Product Catalogue




5RS095/093/115/116
P01-02




5RS091/092/117/118
P03-04




5RS039
P05-10




5RS067
P11



5RS058
P12




5RS063
P13




5RS114
P16



5RS104
P17-18




5RS105
P19




5RS106
P20




5RS061
P22




5RS060-1
P23




5RS060-2
P24




5RS015/019
P25




5RS086
P26




5RS102
P27



5RS113
P28




5RS082-1
P29



5RS082-2
P31




5RS100
P32





5RS098-1
P34





5RS095/5RS093/5RS115/5RS117 *New!*


Power	Size (A×B)	Cutout	Lumen
8 / 10 W	110×55mm	90-95mm	960 lm
15/18 W	150×68mm	130-135mm	1425 lm
25/30 W	172×88mm	150-165mm	1900 lm
30/35 W	228×98mm	200-210mm	2375 lm



CCT Changeable

3000K 4000K 6000K

Loop In/Out





RADIANT LIGHTING



5RS096/5RS094/5RS116/5RS118 *New!*


Power	Size (A×B)	Cutout	Lumen
8 / 10 W	110×55mm	90-95mm	750 lm
15/18 W	150×68mm	130-135mm	1350 lm
25/30 W	172×88mm	150-165mm	1800 lm
30/35 W	228×98mm	200-210mm	2150 lm



Variable Beam Angle

30°/60°


Loop In/Out



5RS091 / 5RS092 / 5RS119 / 5RS121 *New!*

Power & Size (A×B) & Cutout & Lumen

8 W	110×70mm	90-95mm	760 lm
13W	150×84mm	125-135mm	1235 lm
18W	172×95mm	150-165mm	1710 lm
25W	228×98mm	200-210mm	2375 lm



CCT Changeable

3000K 4000K 6000K

Loop In/Out





APP CONTROLLED LED DOWNLIGHT With Stunning Ambient Glow Lighting

MARKET LEADING LED DOWNLIGHT



10W - 12W LED Downlight
Fully Dimmable 0-100%





2200 - 6300K Fully Tunable
Colour Temperature



IP65 Rated Fascia
Fire Rated 30, 60 & 90 mins.



5 Year Warranty
50,000h + Life



AMBIENT GLOW LIGHTING

Enables unique halo lighting in every room.



Stunning Glow Light Effect
Fully Dimmable 0-100%




Ambient Light Available In:
3W Full Spectrum RGB; or
2-6W 2200-6300K CCT

TOTAL WIRELESS CONTROL

Control from the D1 App or D1 Smart Switch



Free Smartphone & Tablet App
Expandable Bluetooth Mesh Network





Optional Smart Switch
Provides Direct Room Control



RADIANT LIGHTING


/ 05






D1-RGB

10W Tuneable CCT Main Light
3W RGB Halo Light
65-70mm Cut Out



D1-CCT

10W Tuneable CCT Main Light
2-6W CCT Halo Light
65-70mm Cut Out



D1-Large-RGB

12W Tuneable CCT Main Light
3W RGB Halo Light
90-95mm Cut Out



D1-Large-CCT

12W Tuneable CCT Main Light
2-6W CCT Halo Light
90-95mm Cut Out



C1

10W Tuneable CCT Main Light
65-70mm Cut Out




C1-Large

12W Tuneable CCT Main Light
90-95mm Cut Out



D1 Smart Switch

Compatible with D1 and can also control C1 products for mixed installations.




C1 Smart Switch

Compatible with C1 products ONLY.

CONTACT US



White Label Lighting Limited
T: +44(0)113 234 0753
E: win@white-label-lighting.co.uk



RADIANT LIGHTING



APP CONTROLLED LED DOWNLIGHT WITH STUNNING AMBIENT GLOW LIGHTING



70mm Cut Out

90mm Cut Out

Item	D1-RGB	D1-CCT	D1-RGB-LARGE	D1-CCT-LARGE
Power Rating	10W Dual Colour	10W Dual Colour	12W Dual Colour	12W Dual Colour
EC Energy Consumption	10kWh / 1000h	10kWh / 1000h	12kWh / 1000h	12kWh / 1000h
Main Light Colour	2200 - 6300k	2200 - 6300k	2200 - 6300k	2200 - 6300k
Halo Light Colour	Full colour spectrum	2200 - 6300k	Full colour spectrum	2200 - 6300k
Main Light Lumen	650-780lm	650-780lm	800-900lm	800-900lm
Beam Angle	40° 2185 cd	40° 2185 cd	60° 2185 cd	60° 2185 cd
CRI	> 80	> 80	> 80	> 80
Lifespan	50,000 hrs	50,000 hrs	50,000 hrs	50,000 hrs
Housing Material	Aluminum + PC	Aluminum + PC	Aluminum + PC	Aluminum + PC
Dimensions	55 x 85 x 85 mm (Ex. Driver)	55 x 85 x 85 mm (Ex. Driver)	55 x 105 x 105 mm (Ex. Driver)	55 x 105 x 105 mm (Ex. Driver)
Cut Out Size	65 - 70 mm	65 - 70 mm	90 - 95 mm	90 - 95 mm
LED Manufacturer	SANAN (Custom Made)	SANAN (Custom Made)	SANAN (Custom Made)	SANAN (Custom Made)
Power Factor	> 0.5	> 0.5	> 0.5	> 0.5
Working Temperature	-30°C to +35°C	-30°C to +35°C	-30°C to +35°C	-30°C to +35°C
Voltage Range	AC 110 - 240 V	AC 110 - 240 V	AC 110 - 240 V	AC 110 - 240 V
Constant Current Driver	YES	YES	YES	YES
PCB Material (MCPCB/FR4)	MCPCB	MCPCB	MCPCB	MCPCB
Isolated/Non-Isolated	Isolated	Isolated	Isolated	Isolated
Dimmable	YES via APP	YES via APP	YES via APP	YES via APP
Fire Rated	30, 60 & 90 minutes	30, 60 & 90 minutes	30, 60 & 90 minutes	30, 60 & 90 minutes
Warranty	5 Years	5 Years	5 Years	5 Years
Building Regs Part L	YES	YES	YES	YES
Standard Certification	CE, RoSH	CE, RoSH	CE, RoSH	CE, RoSH



All sales are subject to standard Terms and Conditions that can be viewed on our website.
Certification for local markets is the buyers sole responsibility.

RADIANT LIGHTING



D1 SMART SWITCH



MAINS POWERED ROOM CONTROLLER FOR D1 DOWNLIGHTS



Provides room control for D1 fittings.

(App required for initial setup).

- ✓ Independent main light and halo light control.
- ✓ Full colour and brightness control.
- ✓ Touch sensitive fascia.
- ✓ Wireless Bluetooth signalling to light group.
- ✓ Compatible with D1 & C1 products in mixed installations.



Item	D1-SWITCH-UK
Current Max.	10A
Voltage Rating	240V
External Dims.	85x85x6mm
Back Box Size	35mm
Fixing Holes	4mm
Compatible Products	D1-RGB D1-CCT D1-LARGE-RGB D1-LARGE-CCT C1 C1-LARGE

All sales are subject to standard Terms and Conditions that can be viewed on our website. Certification for local markets is the buyers sole responsibility.




RADIANT LIGHTING



APP CONTROLLED LED DOWNLIGHT

FIRE RATED, IP65, FULLY TUNABLE & DIMMABLE



Item	C1	C1-Large
Power Rating	10W Dual Colour	12W Dual Colour
Selectable Light Colour	2200 - 6300k	2200 - 6300k
Light Lumen	650-780lm	800-900lm
Beam Angle	40° 2185 cd	60° 2185 cd
CRI	> 80	> 80
Average Lifespan	50,000 hrs	50,000 hrs
Housing Material	Aluminum + PC	Aluminum + PC
Dimensions	55 x 85 x 85 mm (Ex. Driver)	55 x 105 x 105 mm (Ex. Driver)
Cut Out Size	67 - 70 mm	90 mm
LED Manufacturer	SANAN (Custom Made)	SANAN (Custom Made)
Power Factor	> 0.5	> 0.5
Working Temperature	-30°C to +35°C	-30°C to +35°C
Voltage Range	AC 110 - 240 V	AC 110 - 240 V
IC Based Constant Current Driver	YES	YES
PCB Material (MCPCB/FR4)	MCPCB	MCPCB
Isolated/Non-Isolated	Isolated	Isolated
Dimmable	YES via App	YES via App
Fire Rated	30, 60 & 90 minutes	30, 60 & 90 minutes
EC Energy Consumption	10kWh / 1000h	12kWh / 1000h
Warranty	3 Years	3 Years
Building Regs Part L	YES	YES
Manufacturers Standard Certification	CE, RoSH	CE, RoSH





All sales are subject to standard Terms and Conditions that can be viewed on our website. Certification for local markets is the buyers sole responsibility.



C1 SMART SWITCH



MAINS POWERED ROOM CONTROLLER FOR C1 DOWNLIGHTS



Provides room control for C1 fittings.

(App required for initial setup).

- ✓ Full colour and brightness control.
- ✓ Touch sensitive fascia.
- ✓ Wireless Bluetooth signalling to light group.
- ✓ Compatible with C1 products ONLY.



Fits in standard 35mm back box

Item	C1-SWITCH-UK
Current Max.	10A
Voltage Rating	240V
External Dims.	85x85x6mm
Back Box Size	35mm
Fixing Holes	4mm
Compatible Products	C1 C1-LARGE



All sales are subject to standard Terms and Conditions that can be viewed on our website. Certification for local markets is the buyers sole responsibility.



5RS067

Power & Size (A×B) & Cutout


4W	86×55mm	55-70mm
6W	86×55mm	55-70mm



 **Easy Fit Magnetic Bezel**




RADIANT LIGHTING



 Easy Fit Magnetic Bezel

5RS058

Power & Size (AxB) & Cutout
 6W 86x74.58 mm 55-70mm




 600 lm	 Dimmable	 CRI 80	 AC 220-240V	 IC
 IP65 Fascia	 40°	 Fire Rated	 3 YEARS	



5RS063

Power & Size (A×B) & Cutout
6W 86.4×81.5mm 70mm





RADIANT LIGHTING



RADIANT LIGHTING



5RS114 *New!*


Power & Size (A×B) & Cutout

7W 89.96×52.9mm 65-75mm

CCT Changeable & Dim to warm

3000K 4000K & 2000K~3000K






CCT Changeable & Dim to warm

5RS104 *New!*

Power & Size (A×B) & Cutout
 7W 88×53.4 mm 65-70mm






 Easy Fit Magnetic Bezel


Loop In/Out



Plug-n-play Connector















5RS105 *New!*

Power & Size (A×B) & Cutout
 10W 84×51.5mm 65-70mm



CCT Changeable & Dim to warm
 3000K 4000K & 2000K~3000K

- 
800-850 lm
- 
Dimmable
- 
CRI 80
- 
AC 220-240V
- 
20°
- 
100000
- 
Low glare
- 
60°
- 
Fire Rated
- 
3 YEARS




RADIANT LIGHTING












5RS106 *New!*



Power & Size (A×B) & Cutout
 10W 83×51.5mm 65-70 mm



CCT Changeable & Dim to warm
 3000K 4000K & 2000K~3000K

-  800-850 lm
-  Dimmable
-  CRI 80
-  AC 220-240V
-  Low glare
-  100000
-  IP65
-  60°
-  Fire Rated
-  3 YEARS
-  Emergency version (optional)





RADIANT LIGHTING



5RS061 *New!*

Power & Size (A×B) & Cutout

10W

82×60mm

70mm



CCT Changeable & Dim to warm



3000K 4000K & 2000K~3000K






5RS060-1

Power & Size (A×B) & Cutout
 10W 86.22×60.3mm 70mm



CCT Changeable

3000K 4000K 6000K





CCT Changeable

3000K 4000K 6000K



5RS060-2

Power & Size (A×B) & Cutout

10W

94.21×60.8mm

80mm



650-750 lm



Dimmable



CRI
80



AC
220-240V



UGR < 19



100000



For
fixed only



40°/60°



Fire Rated



3
YEARS






20°

5RS015/5RS019

Power & Size (A×B) & Cutout

8W	80×80mm	70mm
10W	80×90mm	70mm






5RS086 *New!*


Power & Size (AxB) & Cutout

12W 106.1x39.3 mm 90mm




CCT Changeable

3000K 4000K 6000K



RADIANT LIGHTING




Easy Fit Magnetic Bezel

5RS102

Power & Size (A×B) & Cutout

12W 106.1×39.3 mm 90mm



CCT Changeable & Dim to warm

3000K 4000K & 2000K~3000K


1150 lm	Dimmable	CRI 80	AC 220-240V	5 YEARS
100000	IP65 Fascia	60°	Fire Rated	

RADIANT LIGHTING



5RS113 *New!*

Power & Size (A×B) & Cutout

12W 106.1×39.3 mm 90mm



Power changable




RADIANT LIGHTING



5RS082

Power & Size (AxB) & Cutout
 8W 115×60.42mm 90-100mm



CCT Changeable

3000K 4000K 6000K

800 lm	Dimmable	CRI 80	AC 220-240V	SMD
100000	IP65 Fascia	60°	IC-4	3 YEARS




RADIANT LIGHTING



5RS082

Power & Size (A×B) & Cutout
 6W 94.83×55.5 mm 70-80mm
 8W 115×60.42 mm 90-100mm

CCT Changeable
 3000K 4000K 6000K





- 600/800 lm
- Dimmable
- CRI 80
- AC 220-240V
- SMD
- 100000
- IP54
- 90°
- IC-4
- 3 YEARS



5RS100

Power & Size (A×B×C) & Cutout
12W 400×48.5×33.8 mm 405×37mm






RADIANT LIGHTING




5RS098

Power & Size (A×B) & Cutout
10W 88.4×54.2mm 70mm



CCT Changeable

3000K 4000K 6000K



NOTE:



© Suzhou Radiant Lighting Technology Co.,Ltd. 2018

Address :

Jiatai Road
Shuanglong Industrial Park
Fenghuang Town
Zhangjiagang, Jiangsu
China

Contact :

P : +86-512-58428167
F : +86-512-58423309
E : sales@cnradiant.com
W : www.radiant-lighting.com